

RIDEMAX IT 696 - Teknik Özellikler



Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	440/80 R 30 IND (16.9 R 30)
LI/SS	157 A8/153 D

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1466
Static Loaded Radius (mm)	668
Rolling Circumference (mm)	4456
SRI (mm)	700
Rim Rec	W 14 L
Rim Alt	W 15 L
ECE	E4-106R-002297

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1715	2115	2480	2885	3250	3650
50	1825	2250	2640	3065	3455	3880
40	1940	2395	2805	3260	3670	4125
30	2020	2495	2925	3395	3825	4300

Printed on 4/23/2024 2:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..