

RIDEMAX IT 696 - Teknik Özellikler



Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	460/65 R 24 IND
LI/SS	151 D/156 A8

Dimensions US Standard

Usa code	94058655
TMPH	1
Section Width (inch)	17.9
Overall Diameter (inch)	47.8
Static Loaded Radius (inch)	21.6
Rolling Circumference (inch)	143.5
Rim Rec	DW 14 L
Rim Alt	DW 15 L ; DW 13

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58
40	3040	3730	4190	4950	5630	6320	6920	7610
30	3280	4030	4520	5350	6080	6820	7480	8220
25	3530	4320	4850	5730	6530	7320	8020	8820
20	3650	4480	5020	5930	6760	7570	8300	9130

Printed on 4/23/2024 12:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..