

RIDEMAX IT 696 - Teknik Özellikler



Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	480/80 R 38 IND (18.4 R 38)
LI/SS	166 A8/161 D

Dimensions US Standard

Usa code	94033867
Section Width (inch)	18.9
Overall Diameter (inch)	68.2
Static Loaded Radius (inch)	30.7
Rolling Circumference (inch)	205.2
Rim Rec	W 15 L
Rim Alt	W 16 L
ECE	E11-106R-004075

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	4790	5920	6930	8060	9070	10200
30	5180	6390	7500	8710	9810	11020
25	5490	6780	7950	9230	10390	11680
20	5720	7050	8280	9610	10840	12170

Printed on 4/23/2024 9:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..