

## RIDEMAX IT 696 - Teknik Özellikler



### Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	540/80 R 42 IND
LI/SS	168 D/173 A8

## Dimensions US Standard

Usa code	94062409
Section Width (inch)	22
Overall Diameter (inch)	76
Static Loaded Radius (inch)	34.6
Rolling Circumference (inch)	231.3
Rim Rec	W 18 L
Rim Alt	W 16 L
ECE	E11-106R-005714

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	5800	7160	8400	9750	10990	12350
30	6270	7740	9070	10540	11870	13340
25	6730	8310	9740	11320	12750	14330
20	8080	9980	11690	13580	15300	17200

Printed on 4/23/2024 1:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..