RIDEMAX IT 697 (M+S) - Teknik Özellikler

Description

RIDEMAX IT 697 M+S kışın yapılan çalışmalar sırasında modern çiftçilik yüklenicilerinin ihtiyaçlarını karşılamak için en iyi yanıttır. Nakliye ve belediye uygulamaları için mükemmeldir. Traktörlerde kullanılan bu kış lastiği, kar zincirleri takmaya gerek kalmadan buzlu ve karlı yollardaki tüm çalışmalarda sıra dışı bir yol tutuş sağlar. Sırt kanalları ve güçlü gövdesi sayesinde, traktör yüksek hızlarda da tam sabitleme ile sürülebilir. Sırt tasarımı, ağır hizmetler için özel olarak geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

International Standard

Construction

RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	460/70 R 24 IND
LI/SS	157A8/152D

Dimensions International Standard

Section Width (mm)	465
Overall Diameter (mm)	1254
Static Loaded Radius (mm)	571
Rolling Circumference (mm)	3772
SRI (mm)	600
Rim Rec	DW 15 L
Rim Alt	DW14 L; DW 16L
ECE	E11-106R-006840

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1775	2170	2380	2805	3160	3550
50	1920	2340	2570	3030	3415	3835
40	2065	2520	2765	3260	3675	4125
30	2130	2600	2855	3370	3795	4260

Printed on 4/25/2024 9:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..