

RM 2002 - Teknik Özellikler



Description

RM 2002 hem yolda hem de arazide, römorklar ve hafif kamyonlarla yapılan taşımacılık faaliyetleri için uygundur. Ürün ömür döngüsü boyunca, uzun süreli dayanıklılık ve yüksek performans sağlar. "Endüstriyel" modeli kaldırma ve taşıma tipi vinçler için idealdir.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Römork

Endüstriyel: Mobil Vinç

Version	INDUSTRIAL
Type	TT
Tyre Size	11.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	302
Overall Diameter (mm)	1101
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

Load capacity (Kg)

	km/h / bar	7.95	7.25
100 LS		3250	-
100 LD		-	2900

Printed on 4/19/2024 11:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..