

RM 2002 - Teknik Özellikler



Description

RM 2002 hem yolda hem de arazide, römorklar ve hafif kamyonlarla yapılan taşımacılık faaliyetleri için uygundur. Ürün ömür döngüsü boyunca, uzun süreli dayanıklılık ve yüksek performans sağlar. "Endüstriyel" modeli kaldırma ve taşıma tipi vinçler için idealdir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Römork

Endüstriyel: Mobil Vinç

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions US Standard

Usa code	94022687
Ply Rating	18
Section Width (inch)	12.4
Overall Diameter (inch)	45.1
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	139.3
Rim Rec	8.5
Rim Alt	8.0 ; 9.0

Load capacity (lbs)

mph / psi	115	105
62 LS	8265	-
62 LD	-	7385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/1/2025 12:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..