

RM 500 - Teknik Özellikler



Description

RM 500, biçerdöver uygulamalarına uygun çelik kuşaklı bir radyal lastiktir. Güçlü bir gövde ve yüksek yük kapasitesi ve özel kesilme ve kopma direnci sağlayan özel bir sırt tasarımına sahiptir. Geniş taban izi sayesinde RM 500, mükemmel çekiş ek olarak daha az toprak sıkışması ile zeminde mükemmel basınç dağılımı sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Biçerdöver

Version	STEEL BELTED
Type	TL
Tyre Size	600/65 R 28
LI/SS	168 A8 / 156 A8
LI/SS DRIVE WHEEL	156 A8
LI/SS FREE ROLLING	168 A8

Dimensions International Standard

Section Width (mm)	590
Overall Diameter (mm)	1486
Static Loaded Radius (mm)	640
Rolling Circumference (mm)	4340
SRI (mm)	700
Rim Rec	W 18 L
Rim Alt	W 20 L
ECE	E11-106R-005993

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0
40 Free Rolling	3080	3530	3980	4820	5600
40 Drive Wheel	2200	2520	2840	3440	4000

Printed on 4/27/2024 12:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..