

ROCK GRIP E4 - Teknik Özellikler



Description

ROCK GRIP (E-4) madencilik hizmetleri ve taş ocağı çalışmalarında kullanılan kamyonlar için özel olarak tasarlanmış, çapraz kuşaklı bir lastiktir. Kısa mesafeli saha şartlarınız hem ısıya karşı dayanıklılık hem de kesilmelerden korunma gerektirdiğinde, ROCK GRIP güvenebileceğiniz lastiktir.

UM

International Standard

Construction

❖ BIAS

Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	24
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4173
Rim Rec	10.00/2.0
TRA Code	E4
Tread Depth	50

Load capacity (Kg)

km/h / bar	5.75
50	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/22/2025 8:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..