

ROCK GRIP E4 - Teknik Özellikler



Description

ROCK GRIP (E-4) madencilik hizmetleri ve taş ocağı çalışmalarında kullanılan kamyonlar için özel olarak tasarlanmış, çapraz kuşaklı bir lastiktir. Kısa mesafeli saha şartlarınız hem ısıya karşı dayanıklılık hem de kesilmelerden korunma gerektirdiğinde, ROCK GRIP güvenebileceğiniz lastiktir.

UM

International Standard

Construction

❖ BIAS

Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD
Type	TL
Tyre Size	16.00 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	470
Overall Diameter (mm)	1525
Static Loaded Radius (mm)	699
Rolling Circumference (mm)	4514
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	E4

Load capacity (Kg)

km/h / bar	6.50	8.75
50	7300	-
10	-	12500

Printed on 11/28/2023 8:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..