

ROCK GRIP E4 - Teknik Özellikler



Description

ROCK GRIP (E-4) madencilik hizmetleri ve taş ocağı çalışmalarında kullanılan kamyonlar için özel olarak tasarlanmış, çapraz kuşaklı bir lastiktir. Kısa mesafeli saha şartlarınız hem ısıya karşı dayanıklılık hem de kesilmelerden korunma gerektirdiğinde, ROCK GRIP güvenebileceğiniz lastiktir.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Sabit kaya kamyonu

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 18.00 - 33 |

Dimensions International Standard

| | |
|-----------------------------------|-----------|
| Ply Rating | 36 |
| Overall Width (mm) | 510 |
| Overall Diameter (mm) | 1887 |
| Static Loaded Radius (mm) | 869 |
| Rolling Circumference (mm) | 5586 |
| Rim Rec | 13.00/2.5 |
| TRA Code | E4 |
| Tread Depth | 60 |

Load capacity (Kg)

| km/h / bar | 6.50 | 8.50 |
|------------|-------|-------|
| 50 | 11200 | - |
| 10 | - | 18500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/22/2025 9:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..