

ROCK GRIP IND4 (ECH) - Teknik Özellikler



Description

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH), endüstriyel elleçleme ve çelik işleri de dahil olmak üzere çeşitli uygulamalarda kullanılan Boş konteyner elleçleme için özel olarak tasarlanmış çapraz katlı bir lastiktir. Özel ROCK GRIP hamuru, müthiş sabitleme ve dayanıklılık ile birlikte özel ısı dayanıklılığı sağlar.

UM

International Standard

Construction

❖ BIAS

Machinery

Endüstriyel: Bş konteyner taşıyıcısı

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	315
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	3755
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND4

Load capacity (Kg)

km/h / bar	9.90
10	9315

Printed on 4/11/2024 3:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..