

## ROCK GRIP L4 - Teknik Özellikler



### Description

ROCK GRIP (L-4) engebeli zemin koşullarındaki ağır yükleme hizmetlerinde kullanılan tekerlekli yükleyici çalışmaları için tasarlanmış, çapraz kuşaklı bir lastiktir. Özel tasarımı, kesilme ve parçalanmaya karşı dayanıklı diş bileşiği delinmeleri en aza indirerek makine çalışmama süresini azaltır. (L-4) diş derinliği daha uzun lastik ömrü sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Endüstriyel: Dozer • Yükleyici

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

## Dimensions International Standard

Ply Rating	24
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4173
Rim Rec	10.00/1.5
TRA Code	L4

## Load capacity (Kg)

km/h / bar	8.50
10	9500

Printed on 4/16/2024 11:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..