

ROCK GRIP (T) - Teknik Özellikler



Description

ROCK GRIP (E-4) özellikle taş ocakları ve kısa mesafeli madencilik uygulamalarında kullanılan yol ve araziye yönelik kamyonlarla ağır yükler taşımak için uygundur. Özel diş bileşiği, en engebeli yer koşullarında kesilme ve delinmeleri en aza indirir. ROCK GRIP (E-4) sıra dışı çekiş gücü ve daha uzun lastik ömrü sunar.

UM

US Standard

Construction

❖ BIAS

Machinery

Yoldışı: Yol ve yol dışı kamyon • Sabit kaya kamyonu

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94035755
Ply Rating	20
Overall Width (inch)	12.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	147.8
Rim Rec	8.5
Rim Alt	8.0

Load capacity (lbs)

mph / psi	115
50 LS/LD	8540

Printed on 4/26/2024 4:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..