

ROCK STAR (SB SPL) - Teknik Özellikler



Description

ROCK STAR hem yolda hem de çelik raylarda kullanılan ekipmanlar için özel olarak tasarlanmıştır. ROCK STAR üstün yük kapasitesi için 32 kat dereceli bir lastiktir. Benzersiz sırt hamuru üstün kesik ve kopma direnci sağlarken çelik kuşaklar dayanıklılık katar.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Karayolu demiryolu ekipmanı

Version	STEEL BELTED SPL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	390
Overall Diameter (mm)	1425
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	14175

Printed on 4/25/2024 6:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..