

RT 851 - Teknik Özellikler



Description

RT 851, çim saha uygulamalarında traktörler için özel olarak tasarlanmış bir R-1 lastiğidir. Özel yuvarlatılmış diş tasarımı, çim sahalara ve gelişmekte olan ürünlere verilen zararı ve toprağın sıkışmasını azaltmak üzere geliştirilmiştir. Sağlam polyester kuşaklara sahip güçlü naylon gövde, olağanüstü çekiş ve daha yüksek yük kapasitesi sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	14.9L R 20 (375/75 R 20)
LI/SS	119 A8/B

Dimensions US Standard

Usa code	94048632
Section Width (inch)	14.9
Overall Diameter (inch)	43.3
Static Loaded Radius (inch)	19.6
Rolling Circumference (inch)	129.4
Rim Rec	W 13
Rim Alt	W 11; W 12; W 14
ECE	E11-106R-002989
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1650	1930	2190	2470	2730	3000
25	1650	1930	2190	2470	2730	3000
20	1770	2060	2360	2650	2930	3220
5 LT	2220	2580	2940	3310	3670	4020
5 HT	1770	2060	2360	2650	2930	3220

Printed on 4/20/2024 12:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..