

RT 853 - Teknik Özellikler



Description

RT 853, toprak işleme ve üzüm hasadı uygulamalarında traktörler ve üzüm hasat makinelerine yönelik bir R-1 lastiğidir. Mükemmel çekiş, yük kapasitesi ve kendi kendini temizleme özelliklerine sahiptir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör • Üzüm hasat makinesi

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 480/80 R 38 (18.4 R 38) |
| LI/SS | 149 A8/B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94045709 |
| Section Width (inch) | 18.7 |
| Overall Diameter (inch) | 68.8 |
| Static Loaded Radius (inch) | 31.2 |
| Rolling Circumference (inch) | 208.7 |
| Rim Rec | W 16 L |
| Rim Alt | W 15 L ; W 14 L |
| ECE | E4-106R-001822 |
| TRA Code | R1 |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| 25 | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| 20 | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |
| 5 LT | 5290 | 6150 | 7010 | 7880 | 8740 | 9600 |
| 5 HT | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |

Printed on 4/23/2024 4:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..