

SAND KING - Teknik Özellikler



Description

SAND KING taşımacılık uygulamalarında kullanılan römorklar için özel olarak tasarlanmış blok desenli bir lastiktir. Kumlu yüzeylerde kusursuz çekiş gücü ve en iyi zemin temasını sağlar.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Römork

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions US Standard

Usa code	94046508
Ply Rating	10
Section Width (inch)	8.5
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	97.3
Rim Rec	5.50 F SDC
Rim Alt	6.00 G
ECE	E11-106R-005309

Load capacity (lbs)

mph / psi	75
40 LS	2680

Printed on 4/24/2024 5:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..