

SAND MASTER - Teknik Özellikler



Description

SAND MASTER römorklar için özel olarak tasarlanmış blok desenli bir lastiktir. Kumlu yüzeylerde kusursuz çekiş gücü ve en iyi zemin temasını sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Römork

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	8
Section Width (mm)	215
Overall Diameter (mm)	820
Rim Rec	5.50 F SDC
Rim Alt	6.00 G
ECE	E11-106R-005308

Load capacity (Kg)

km/h / bar	4.15
65 LS	1090

Printed on 5/1/2024 12:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..