

SAND STAR - Teknik Özellikler



Description

SAND STAR römorklar için özel olarak tasarlanmış blok desenli bir lastiktir. Kumlu yüzeylerde kusursuz çekiş gücü ve en iyi zemin temasını sağlar. Aynı zamanda toprak sıkışmasını da azaltır.

UM

US Standard

Construction



Machinery

Endüstriyel: Römork

Version	STANDARD
Туре	TL
Tyre Size	9.00 - 13
LI/SS	108 D

Dimensions US Standard

Usa code	94031092
Ply Rating	6
Section Width (inch)	9.6
Overall Diameter (inch)	30.9
Rim Rec	5.50 F
Rim Alt	5.50 WB
ECE	E11-106R-005296

Load capacity (lbs)

mph / psi	45
40	2205

Printed on 4/23/2024 2:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..