

## SIERRA MAX - Teknik Özellikler



### Description

SIERRA MAX, hem arazi hem de çim ve bahçe uygulamalarına yönelik BKT lastiğidir. Radyal yapısı, çöl veya kirlı ve kayalık yüzeyler gibi zorlu arazilerde çok daha düzgün ve rahat bir sürüş sağlar. Daha geniş taban iziyle özel sırt tasarımı olağanüstü ileri ve yanal çekiş sağlar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: ATV

Version	STANDARD
Type	TL
Tyre Size	AT 26 X 11 R 14
LI/SS	54 N

## Dimensions International Standard

Section Width (mm)	280
Overall Diameter (mm)	675
Static Loaded Radius (mm)	310
Rolling Circumference (mm)	2027
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005096

## Load capacity (Kg)

km/h / bar	0.50
140	212

Printed on 4/20/2024 7:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..