

SIERRA MAX - Teknik Özellikler



Description

SIERRA MAX, hem arazi hem de çim ve bahçe uygulamalarına yönelik BKT lastiğidir. Radyal yapısı, çöl veya kirlı ve kayalık yüzeyler gibi zorlu arazilerde çok daha düzgün ve rahat bir sürüş sağlar. Daha geniş taban iziyle özel sırt tasarımı olağanüstü ileri ve yanal çekiş sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: ATV

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions International Standard

Section Width (mm)	280
Overall Diameter (mm)	700
Static Loaded Radius (mm)	318
Rolling Circumference (mm)	2091
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005097

Load capacity (Kg)

km/h / bar	0.50
140	224

Printed on 4/20/2024 11:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..