

## SKID POWER ( CHEVRON ) - Teknik Özellikler



### Description

SKID POWER (CHEVRON) inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için özel olarak tasarlanmıştır. Kusursuz çekişin yanı sıra gelişmiş kendini temizleme özelliklerine sahiptir. SKID POWER (CHEVRON) özellikle gevşek yüzeyler için uygundur ve kesilme ve parçalanmaya karşı yüksek dayanıklılık sunar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	7.00 - 15

## Dimensions US Standard

Usa code	94017171
Ply Rating	6
Section Width (inch)	8
Overall Diameter (inch)	30
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	90.4
Rim Rec	5.50 F
Rim Alt	6 LB

## Load capacity (lbs)

mph / psi	60
5	3180
10	2510

Printed on 4/27/2024 10:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..