

SKID POWER HD (A) - Teknik Özellikler

Description

SKID POWER HD (A) inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için tasarlanmıştır. Lastik, kesilme ve parçalanmaya karşı yüksek dayanıklılık ve olağanüstü sağlamlık sağlayan ekstra derin desene ve yanak korumasına sahiptir. SKID POWER HD (A) gevşek yüzeyler ve ağır yük gerektiren işler için ideal lastiktir.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Mini yükleyici



Version	IMPLEMENT
Type	TL
Tyre Size	15 - 19.5
LI/SS	146 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	1019
Static Loaded Radius (mm)	463
Rolling Circumference (mm)	3075
Rim Rec	11.75
Rim Alt	12.25
ECE	E11-106R-003656

Load capacity (Kg)

km/h / bar	4.85
40	3000

Printed on 4/23/2024 3:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..