

SKID POWER HD (A) - Teknik Özellikler

Description

SKID POWER HD (A) inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için tasarlanmıştır. Lastik, kesilme ve parçalanmaya karşı yüksek dayanıklılık ve olağanüstü sağlamlık sağlayan ekstra derin desene ve yanak korumasına sahiptir. SKID POWER HD (A) gevşek yüzeyler ve ağır yük gerektiren işler için ideal lastiktir.

UM

International Standard

Construction

❖ BIAS

Machinery

Endüstriyel: Mini yükleyici



Version	STANDARD
Type	TL
Tyre Size	26 X 12 - 12

Dimensions International Standard

Ply Rating	10
Section Width (mm)	305
Overall Diameter (mm)	660
Static Loaded Radius (mm)	297
Rolling Circumference (mm)	1947
Rim Rec	10.50 I - 55
Rim Alt	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA

Load capacity (Kg)

km/h / bar	4.40
10	1595
15	1260
25	1165

Printed on 4/20/2024 5:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..