

## SKID POWER HD (A) - Teknik Özellikler

### Description

SKID POWER HD (A) inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için tasarlanmıştır. Lastik, kesilme ve parçalanmaya karşı yüksek dayanıklılık ve olağanüstü sağlamlık sağlayan ekstra derin desene ve yanak korumasına sahiptir. SKID POWER HD (A) gevşek yüzeyler ve ağır yük gerektiren işler için ideal lastiktir.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Mini yükleyici



|           |                  |
|-----------|------------------|
| Version   | STANDARD         |
| Type      | TL               |
| Tyre Size | 33 X 15.5 - 16.5 |
| LI/SS     | 151 A2           |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94060825        |
| Ply Rating                   | 14              |
| Section Width (inch)         | 15.5            |
| Overall Diameter (inch)      | 33              |
| Static Loaded Radius (inch)  | 15.2            |
| Rolling Circumference (inch) | 100.9           |
| Rim Rec                      | 13.00           |
| ECE                          | E11-106R-006606 |

## Load capacity (lbs)

| mph / psi | 70   |
|-----------|------|
| 5         | 7600 |
| 10        | 6005 |
| 15        | 5555 |

Printed on 4/20/2024 4:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..