

SKID POWER HD (B) - Teknik Özellikler



Description

SKID POWER HD (B) inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için tasarlanmıştır. Lastik, kesilme ve parçalanmaya karşı yüksek dayanıklılık ve olağanüstü sağlamlık sağlayan ekstra derin desene ve yanak korumasına sahiptir. SKID POWER HD (B) gevşek yüzeyler ve ağır yük gerektiren işler için ideal lastiktir.

UM

US Standard

Construction

 BIAS

Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	18 X 8.5 - 10
LI/SS	96 A2

Dimensions US Standard

Usa code	94017751
Ply Rating	8
Section Width (inch)	8.1
Overall Diameter (inch)	18.3
Static Loaded Radius (inch)	8.3
Rolling Circumference (inch)	54.8
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-006774

Load capacity (lbs)

mph / psi	44
5	1590
10	1260
15	1160

Printed on 4/23/2024 5:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..