

SKID POWER PLUS - Teknik Özellikler



Description

SKID POWER PLUS inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için tasarlanmıştır. Daha geniş çekmelere sahip lastik kusursuz çekişin yanı sıra gelişmiş kendini temizleme özellikleri sağlar. Lastik, kesilme ve parçalanmaya karşı yüksek dayanıklılık ve olağanüstü sağlamlık sağlayan ekstra derin desen ile gelişmiş yanak korumasına sahiptir. SKID POWER PLUS gevşek yüzeyler için ideal lastiktir. Geniş temas alanı çalışmalar sırasında kusursuz istikrar sağlar.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	8
Section Width (mm)	252
Overall Diameter (mm)	775
Rim Rec	8.25

Load capacity (Kg)

	km/h / bar	4.10
	10	1880
	15	1485
	25	1370

Printed on 4/27/2024 6:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..