

SKID POWER SK - Teknik Özellikler



Description

SKID POWER SK inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için özel olarak tasarlanmıştır. Yanak ve jant korumaları ile derin deseni daha uzun lastik ömrü sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Mini yükleyici

Version	IMPLEMENT
Type	TL
Tyre Size	12 - 16.5
LI/SS	125 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	312
Overall Diameter (mm)	825
Static Loaded Radius (mm)	375
Rolling Circumference (mm)	2434
Rim Rec	9.75
ECE	E11-106R-003545

Load capacity (Kg)

km/h / bar	4.50
40	1650

Printed on 4/24/2024 4:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..