

## SM 55 L5S - Teknik Özellikler



### Description

SM 55 (L-5S) yeraltı madenciliği çalışmaları için ideal, çapraz kuşaklı bir lastiktir. Özel tasarımı, kesilme ve parçalanmaya karşı dayanıklı diş bileşimi delinmeleri en aza indirerek makine çalışmaya süresini azaltır. Ekstra derin L-5 diş derinliği daha uzun lastik ömrünü garanti eder. Lastiğin çelik kuşaklı bir modeli de bulunmaktadır.

### UM

US Standard

### Construction

 BIAS

### Machinery

Yoldışı: Düşük profilli damperli kamyon • Yeraltı madenciliği aracı

Version	STANDARD
Type	TL
Tyre Size	17.5 - 25

## Dimensions US Standard

Usa code	94025886
Ply Rating	20
Overall Width (inch)	17.2
Overall Diameter (inch)	54.1
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	159.2
Rim Rec	14.00/1.5
Rim Alt	14.00/1.3 ; 14.00/1.4 (DC)
TRA Code	L5S

## Load capacity (lbs)

mph / psi	83
5	18200
10	15800
15	14600

Printed on 4/23/2024 1:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..