

SM 55 L5S - Teknik Özellikler



Description

SM 55 (L-5S) yeraltı madenciliği çalışmaları için ideal, çapraz kuşaklı bir lastiktir. Özel tasarımı, kesilme ve parçalanmaya karşı dayanıklı diş bileşiği delinmeleri en aza indirerek makine çalışmaya süresini azaltır. Ekstra derin L-5 diş derinliği daha uzun lastik ömrünü garanti eder. Lastiğin çelik kuşaklı bir modeli de bulunmaktadır.

UM

US Standard

Construction

 BIAS

Machinery

Yoldışı: Düşük profilli damperli kamyon • Yeraltı madenciliği aracı

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 17.5 - 25 |

Dimensions US Standard

| | |
|------------------------------|----------------------------|
| Usa code | 94030651 |
| Ply Rating | 24 |
| Overall Width (inch) | 17.2 |
| Overall Diameter (inch) | 54.1 |
| Static Loaded Radius (inch) | 24.8 |
| Rolling Circumference (inch) | 159.2 |
| Rim Rec | 14.00/1.5 |
| Rim Alt | 14.00/1.3 ; 14.00/1.4 (DC) |
| TRA Code | L5S |

Load capacity (lbs)

| mph / psi | 98 |
|-----------|-------|
| 5 | 20000 |
| 10 | 17400 |
| 15 | 16000 |

Printed on 4/23/2024 11:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..