

## SM 55 L5S - Teknik Özellikler



### Description

SM 55 (L-5S) yeraltı madenciliği çalışmaları için ideal, çapraz kuşaklı bir lastiktir. Özel tasarımı, kesilme ve parçalanmaya karşı dayanıklı diş bileşiği delinmeleri en aza indirerek makine çalışmama süresini azaltır. Ekstra derin L-5 diş derinliği daha uzun lastik ömrünü garanti eder. Lastiğin çelik kuşaklı bir modeli de bulunmaktadır.

### UM

International Standard

### Construction

 BIAS

### Machinery

Yoldışı: Düşük profilli damperli kamyon • Yeraltı madenciliği aracı

Version	STEEL BELTED
Type	TL
Tyre Size	26.5 - 25

## Dimensions International Standard

Ply Rating	28
Overall Width (mm)	700
Overall Diameter (mm)	1798
Static Loaded Radius (mm)	816
Rolling Circumference (mm)	5322
Rim Rec	22.00/3.0
TRA Code	L5S

## Load capacity (Kg)

	km/h / bar	4.75
	10	15500
	15	13485
	25	12400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/4/2024 4:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..