

SM 55 L5S - Teknik Özellikler



Description

SM 55 (L-5S) yeraltı madenciliği çalışmaları için ideal, çapraz kuşaklı bir lastiktir. Özel tasarımı, kesilme ve parçalanmaya karşı dayanıklı diş bileşiği delinmeleri en aza indirerek makine çalışmaya süresini azaltır. Ekstra derin L-5 diş derinliği daha uzun lastik ömrünü garanti eder. Lastiğin çelik kuşaklı bir modeli de bulunmaktadır.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Düşük profilli damperli kamyon • Yeraltı madenciliği aracı

Version	STANDARD
Type	TT
Tyre Size	9.50 - 20

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	275
Overall Diameter (mm)	1065
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3280
Rim Rec	7.5
TRA Code	L5S

Load capacity (Kg)

km/h / bar	8.00
10	4250

Printed on 4/23/2024 4:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..