

SNOW - EXCEL - Teknik Özellikler



Description

SNOW-EXCEL özellikle kış koşullarında yoldaki endüstriyel ve inşaat uygulamaları için uygundur. Mükemmel çekiş sağlar ve buzlu ve karlı çalışmalar için idealdir. Özel olarak tasarlanan sırt deseni sayesinde patinaj riski ortadan kalkar.

UM

International Standard

Construction

❖ BIAS

Machinery

Endüstriyel: Traktör

Version	STANDARD
Type	TL
Tyre Size	16.9 - 24
LI/SS	149 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	445
Overall Diameter (mm)	1320
Static Loaded Radius (mm)	607
Rolling Circumference (mm)	3978
SRI (mm)	625
Rim Rec	DW 15 L
Rim Alt	DW 14 L

Load capacity (Kg)

km/h / bar	2.60
40	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/15/2024 1:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..