

ST 180 - Teknik Özellikler



Description

ST 180, römorklar ve uygulamalı makineler ile taşıma uygulamaları için geliştirilmiş bir lastiktir. Özel sırt deseni sayesinde aşınma azalır ve daha uzun lastik kullanım ömrü sağlanır. ST 180 farklı versiyonlarda sunulmaktadır: "aramid kuşaklı" versiyon geliştirilmiş delinme direnci ve "özel" versiyon yüksek kesilme ve kopmaya karşı direnç sağlar

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	ST 225/75 D 15 (H 78 - 15)

Dimensions International Standard

Ply Rating	8
Section Width (mm)	217
Overall Diameter (mm)	730
Static Loaded Radius (mm)	337
Rolling Circumference (mm)	2178
Rim Rec	6 J
Rim Alt	5½ J ; 6½ J ; 7 J

Load capacity (Kg)

km/h / bar	4.50
40	1150

Printed on 4/19/2024 11:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..