

## ST 180 - Teknik Özellikler



### Description

ST 180, römorklar ve uygulamalı makineler ile taşıma uygulamaları için geliştirilmiş bir lastiktir. Özel sırt deseni sayesinde aşınma azalır ve daha uzun lastik kullanım ömrü sağlanır. ST 180 farklı versiyonlarda sunulmaktadır: "aramid kuşaklı" versiyon geliştirilmiş delinme direnci ve "özel" versiyon yüksek kesilme ve kopmaya karşı direnç sağlar

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	ST 225/75 D 15 (H 78 - 15)

## Dimensions US Standard

Usa code	94018222
Ply Rating	8
Section Width (inch)	8.5
Overall Diameter (inch)	28.7
Static Loaded Radius (inch)	13.3
Rolling Circumference (inch)	85.7
Rim Rec	6 J
Rim Alt	5½ J ; 6½ J ; 7 J

## Load capacity (lbs)

mph / psi	-
-	-

Printed on 4/19/2024 3:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..