

STAR TRAC - Teknik Özellikler



Description

STAR TRAC pamuk çiftliklerindeki hasat makineleri için, ağır yükleri taşıyabilen BKT lastiğidir. Özellikle derin diş deseni sayesinde, hem tarlalarda kusursuz çekiş gücü, hem de yol nakliyatları sırasında kusursuz performans sağlar. Tipik orta boyutlu çalıların bulunduğu pamuk tarlalarında hasat, lastikte kusursuz flotasyon ve azaltılmış toprak sıkışması gibi özelliklerin olmasını gerektirir. Üstelik lastik, kesilme ve bu uygulamanın getireceği fiziksel hasara karşı yüksek dayanıklılık sağlayan özel bir bileşikten üretilmiştir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Pamuk Toplama Makinesi

Version	STANDARD
Type	TL
Tyre Size	DW 500/95 D 32
LI/SS	162 A8/169 A5

Dimensions US Standard

Usa code	94041404
Section Width (inch)	19.7
Overall Diameter (inch)	72.3
Static Loaded Radius (inch)	31.9
Rolling Circumference (inch)	209.6
Rim Rec	13.00 DW

Load capacity (lbs)

mph / psi	26
25	10470
15	12790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/20/2025 2:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..