

STEER GRIP - Teknik Özellikler



Description

STEER GRIP yol ve araziye yönelik kamyonlar için kusursuz direksiyon aksı donanımdır. Düz çekmeli geniş orta diş, lastiği serbest dönüş uygulamaları için uygun kılar ve yol harici ıslak ve kuru koşullarda gelişmiş çekiş gücü sağlar. Özel diş bileşiği aşınmaya karşı en iyi dayanıklılığı ve kesilme ve parçalanmaya karşı direnci bir araya getirecek şekilde tasarlanmıştır, güçlü gövde ise daha uzun lastik ömrü sunar.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Yol ve yol dışı kamyon

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	310
Overall Diameter (mm)	1248
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3785
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.90
80 LS/LD	3875

Printed on 4/28/2024 4:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..