

SUPER GRADER - Teknik Özellikler



Description

SUPER GRADER (G-2) greyderler için özel olarak tasarlanmış, konvansiyonel bir lastiktir. Kusursuz çekiş ve kendini temizleme özellikleri sunar. SUPER GRADER daha uzun lastik ömrü ve ağır yük gerektiren işlere uygunluk sağlayan özel bir bileşikten üretilmiştir.

UM

International Standard

Construction

✦ BIAS

Machinery

Yoldışı: Greyder

Version	STANDARD
Type	TL
Tyre Size	16.00 - 24

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	430
Overall Diameter (mm)	1450
Static Loaded Radius (mm)	644
Rolling Circumference (mm)	4307
Rim Rec	10.00 VA SDC
TRA Code	G2

Load capacity (Kg)

km/h / bar	3.00
40	4500

Printed on 4/26/2024 8:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..