

SUPER SAND - Teknik Özellikler



Description

SUPER SAND özellikle kumlu zeminlerde, sıcak hava koşullarında çalışan römorklar için uygundur. Yüksek flotasyon kabiliyetine sahiptir ve yüksek seviyede yol tutuş gerektiren tüm işler için idealdir.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Römork

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions US Standard

Usa code	94025763
Ply Rating	16
Section Width (inch)	15.2
Overall Diameter (inch)	48.2
Rim Rec	10.00 V
Rim Alt	10.00 W

Load capacity (lbs)

mph / psi	70
40 LS	7805
40 LD	6865

Printed on 4/26/2024 6:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..