

## SUPER SAND - Teknik Özellikler



### Description

SUPER SAND özellikle kumlu zeminlerde, sıcak hava koşullarında çalışan römorklar için uygundur. Yüksek flotasyon kabiliyetine sahiptir ve yüksek seviyede yol tutuş gerektiren tüm işler için idealdir.

### UM

International Standard

### Construction

 BIAS

### Machinery

Endüstriyel: Römork

Version	STANDARD
Type	TT
Tyre Size	16.00 - 20

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	415
<b>Overall Diameter (mm)</b>	1305
<b>Rim Rec</b>	10.00 W

## Load capacity (Kg)

km/h / bar	2.50
50	3650

Printed on 4/23/2024 6:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..