

SUPER TRAX HD - Teknik Özellikler



Description

SUPER TRAX HD, liman ve madencilik uygulamaları da dahil olmak üzere ağır hizmet tipi malzeme elleçleme operasyonlarındaki forkliftler için özel olarak tasarlanmıştır. Ekstra derin sırt, aşınmaya dayanıklı benzersiz bir sırt hamurundan yapılmıştır ve daha uzun kullanım ömrü sağlar. SUPER TRAX HD, kaldırma modunda hem mükemmel sabitleme hem de manevra sağlayan güçlü bir gövde ve güçlendirilmiş yanağa sahiptir. Özel olarak tasarlanmış jant koruyucusu, jant flanşı bölgesinde lastik patlamalarına ve tekerlek hasarına karşı koruma sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Forklift

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.00 - 9 |

Dimensions International Standard

| | |
|----------------------------|--------|
| Ply Rating | 12 |
| Section Width (mm) | 168 |
| Overall Diameter (mm) | 548 |
| Static Loaded Radius (mm) | 256 |
| Rolling Circumference (mm) | 1672 |
| Rim Rec | 4.00 E |

Load capacity (Kg)

| km/h / bar | 10.00 |
|--------------------|-------|
| 25 LOAD WHEEL | 1885 |
| 25 STEER WHEEL | 1450 |
| 10 OTHER VEHICLES | 1885 |
| 25 OTHER VEHICLES | 1450 |
| STATIC SIDE LOADER | 2190 |

Printed on 4/28/2024 11:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..