

## SURE TRAX HD - Teknik Özellikler



### Description

SURE TRAX HD inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için blok desenli bir lastiktir. Üstün jant korumasının yanı sıra kesilme ve parçalanmaya karşı kusursuz dayanıklılık sunar. SURE TRAX HD asfalt yüzeyler ve ağır yük gerektiren işler için idealdir.

### UM

International Standard

### Construction

 BIAS

### Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	268
Overall Diameter (mm)	785
Static Loaded Radius (mm)	359
Rolling Circumference (mm)	2316
Rim Rec	8.25
ECE	

## Load capacity (Kg)

	km/h / bar	5.20
	10	2135
	15	1685
	25	1560

Printed on 4/25/2024 3:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..