

TERRA TRAX - Teknik Özellikler

Description

TERRA TRAX, yem ve besleme uygulamaları için özel olarak tasarlanmıştır. Yolda ve yol dışında kullanım için en uygundur. TERRA TRAX, mükemmel yol performansı, sürüş konforu ve kendi kendini temizleme özellikleri sunar. Düşük yuvarlanma direnci daha iyi yakıt ekonomisine katkıda bulunur.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine



Version	STANDARD
Type	TL
Tyre Size	400/45L - 17.5
LI/SS	156 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	395
Overall Diameter (mm)	785
Static Loaded Radius (mm)	361
Rolling Circumference (mm)	2370
Rim Rec	14.00
ECE	E11-106R-006002

Load capacity (Kg)

km/h / bar	6.00
40	4000

Printed on 4/27/2024 4:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..