

TF 8181 IND - Teknik Özellikler



Description

TF 8181 IND endüstriyel römork uygulamaları için tasarlanmış arazi ve yol lastiğidir. Bu lastik mükemmel direksiyon performansı sağlar.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Römork

Version	INDUSTRIAL
Type	TT
Tyre Size	6.50 - 16
LI/SS	88 A8

Dimensions US Standard

Usa code	94055074
Ply Rating	6
Section Width (inch)	7.1
Overall Diameter (inch)	30.3
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	90.4
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F ; 5.50 F
TRA Code	F2

Load capacity (lbs)

mph / psi	48
25	1230

Printed on 5/8/2024 3:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..