

## TF 8181 - Teknik Özellikler



### Description

TF 8181, toprak işleme ve taşıma uygulamalarında kullanılan tek çeker traktörler için tasarlanmış bir arazi ve yol lastiğidir. Bu lastik mükemmel direksiyon performansı sağlar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Tek çeker traktör  
Endüstriyel: Römork

Version	SPECIAL
Type	TT
Tyre Size	5.00 - 16
LI/SS	76 A8

## Dimensions US Standard

Usa code	94027774
Ply Rating	6
Section Width (inch)	5.5
Overall Diameter (inch)	26.8
Static Loaded Radius (inch)	12.7
Rolling Circumference (inch)	79.7
Rim Rec	4.00 E
Rim Alt	3.00 D ; 4 J ; 4½ J
ECE	E11-106R-004090
TRA Code	F2

## Load capacity (lbs)

mph / psi	62
25	880

Printed on 4/23/2024 1:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..