

TF 9090 - Teknik Özellikler



Description

TF 9090, toprak işleme operasyonlarında kullanılan küçük traktörler için tasarlanmış bir lastiktir. Özel sırt tasarımı, gevşek zeminlerde mükemmel direksiyon performansı sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Küçük Traktör
Endüstriyel: Römork

Version	SPECIAL
Type	TT
Tyre Size	11.00 - 16
LI/SS	118 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	320
Overall Diameter (mm)	970
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	2890
Rim Rec	W 10 L
Rim Alt	W 8 ; W 8 L
ECE	E11-106R-004316
TRA Code	F2

Load capacity (Kg)

km/h / bar	2.50
30	1320

Printed on 4/23/2024 4:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..