

TF 9090 - Teknik Özellikler



Description

TF 9090, toprak işleme operasyonlarında kullanılan küçük traktörler için tasarlanmış bir lastiktir. Özel sırt tasarımı, gevşek zeminlerde mükemmel direksiyon performansı sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Küçük Traktör
Endüstriyel: Römork

Version	STANDARD
Type	TT
Tyre Size	5.00 - 15
LI/SS	82 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	140
Overall Diameter (mm)	655
Static Loaded Radius (mm)	307
Rolling Circumference (mm)	1951
Rim Rec	4.00 E
Rim Alt	3.00 D ; 4 J ; 4½ J
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	475

Printed on 12/11/2023 4:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..