

## TF 9090 - Teknik Özellikler



### Description

TF 9090, toprak işleme operasyonlarında kullanılan küçük traktörler için tasarlanmış bir lastiktir. Özel sırt tasarımı, gevşek zeminlerde mükemmel direksiyon performansı sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Küçük Traktör  
Endüstriyel: Römork

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	111 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	257
Overall Diameter (mm)	855
Static Loaded Radius (mm)	398
Rolling Circumference (mm)	2548
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E4-106R-002668
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.10
30	1090

Printed on 12/10/2023 5:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..