

## TF 9393 - Teknik Özellikler



### Description

TF 9393, toprak işleme uygulamalarında kullanılan küçük traktörler için özel olarak tasarlanmış bir tarımsal ön lastiktir ve özellikle gevşek topraklara uygundur. Sırtı, geniş bir orta kısma ve omuz kuşaklarına sahiptir. Özel sırt tasarımı, tüm yüzeylerde mükemmel direksiyon performansı sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Küçük Traktör

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	210
Overall Diameter (mm)	810
Rim Rec	5.50 F
Rim Alt	5.00 F ; 6.00 F
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.70
30	875

Printed on 4/26/2024 12:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..